

Utilisation de dialog

[http://translate.google.com/translate?hl=fr&sl=auto&tl=fr&u=http%3A%2F%2Flinuxcommand.org%2Ffc3_adv_dialog.php] Commande Dialog]]

[man dialog en Français](#)

[doc dialog en francais](#)

[Exemples Dialog sur github FR Lien Github](#)

man dialog EN
Man dialog FR

exemples

[test001.txt](#)

```
#!/bin/bash

cmd=(dialog --separate-output --checklist "Select options:" 22 76 16)
options=(
  1 "Check disk space" on
  2 "List users currently logged in" off
  3 "Show system uptime" off
)
choices=$("${cmd[@]}" "${options[@]}" 2>&1 >/dev/tty)
clear
for choice in $choices
do
  case $choice in
    1)
      df -h
      ;;
    2)
      who
      ;;
    3)
      uptime
      ;;
  esac
done
```

Rendre executable le script et le lancer

```
chmod +x disk_check.sh  
./disk_check.sh
```

From:
<https://www.magenealogie.chanterie37.fr/www/fablab37110/> - Castel'Lab le Fablab MJC de Château-Renault

Permanent link:
<https://www.magenealogie.chanterie37.fr/www/fablab37110/doku.php?id=start:rasberry:dialog&rev=1785557205>

Last update: **2026/08/01 06:06**

